## AMENDMENTS TO THE CLAIMS

The following is a complete, marked up listing of revised claims with a status identifier in parentheses, underlined text indicating insertions, and strikethrough and/or double-bracketed text indicating deletions.

## Listing of the Claims:

1. (Currently Amended) A pump for conveying a pumped fluid using an actuating fluid, the pump comprising:

a rigid outer casing defining an interior space, and

a tube structure accommodated in the interior space, the tube structure being flexible and substantially inelastic, the an interior of the tube structure defining a pumping chamber for receiving pumped fluid, the tube structure being movable between laterally expanded and collapsed conditions for varying the volume of the pumping chamber thereby to provide discharge and intake strokes, the tube structure being maintained in a taut condition between the ends thereof, the a region of the interior space surrounding the tube structure defining an actuating region for receiving and accommodating actuating fluid, the pumping chamber being adapted configured to receive pumped fluid to cause the tube structure to move towards the expanded condition and the pumping chamber thereby undergoing an intake stroke, the pumping chamber undergoing a discharge stroke upon collapsing of the tube structure in response to the an action of actuating fluid in the actuating region.

wherein one end of the tube structure is closed and the other end is connected to a port through which pumped fluid enters into and discharges from the pumping chamber as the pumping chamber performs intake and discharge strokes and the tube structure is movably supported to accommodate longitudinal extension and

## contraction of the tube structure.

- 2. (Canceled)
- 3. (Currently Amended) A pump according to claim 1, wherein the tube structure is supported at the closed end thereof.
  - 4. (Canceled)
- 5. (Currently Amended) A pump according to claim 2–1, wherein the closed end of the tube structure is movably supported-in any appropriate fashion such as by way of a spring mechanism.
- 6. (Currently Amended) A pump according to claim 2-1, wherein the actuating region comprises-includes an actuating annulus substantially surrounding the tube structure and an actuating chamber located at the closed end of the pump.
  - 7. (Currently Amended) A pump according to claim 6 wherein, the actuating annulus is in fluid communication with the actuating chamber.
  - 8. (Currently Amended) A pump according to claim 1, <u>further comprising</u>: a <u>means device</u> to bleed fluid, such as air, from the pump.
  - 9. (Currently Amended) A pump according to claim 8, <u>further comprising:</u>

    <u>a separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device to bleed air from the pumping chamber and the separate means device the separate means device to bleed air from the separate means device the separate means devic</u>

actuating region, wherein the air is bled from the pumping chamber during the intake stroke and air is bled from the actuating region during the discharge stroke.

- 10. (Currently Amended) A pump according to claim 1, further comprising:
- a monitoring <u>means\_device</u> to monitor the pump during the intake and discharge stroke.
- 11. (Currently Amended) A pump according to claim 10, wherein the monitoring means device monitors the condition of the tube structure.
- 12. (Currently Amended) A pump according to claim 10, wherein the monitoring means—device monitors, directly or indirectly, the position of the closed end of the tube structure.
- 13. (Currently Amended) A pump according to claim 10, wherein the monitoring means-device monitors the pressure differential between components of the pump.
- 14. (Currently Amended) A pump according to claim 10, wherein the monitoring means-device at least indicates when the discharge and intake strokes have been completed.
  - 15. (Currently Amended) A pumping system comprising:
  - a pump in accordance with claim 1-;
  - a delivery means-device for delivering pumped fluid to the pumping chamber

in timed sequence for causing the pumping chamber to undergo an intake stroke—; and

<u>a means device</u> for supplying actuating fluid to the actuating region in timed sequence to cause the tube structure to laterally collapse whereby the pumping chamber undergoes a discharge stroke.

- 16. (Currently Amended) A pumping system according to claim 15, wherein the delivery means-device comprises a delivery pump.
- 17. (Currently Amended) A pumping system <u>according to claim 15</u>, wherein the actuating fluid is <del>of any appropriate form, such as one of hydraulic oil or and water.</del>
- 18. (Currently Amended) A pumping system according to claim 17, wherein the actuating fluid is hydraulic oil.
- 19. (Currently Amended) A pumping system according to claim 18, wherein the supply means—device includes a hydraulic circuit incorporating a reservoir for hydraulic oil and a hydraulic pump.
- 20. (Currently Amended) A pumping system according to claim 19, wherein the hydraulic circuit also includes an intake and exit valve system for regulating the delivery of hydraulic oil into, and the discharge of hydraulic oil from, the actuating region in timed sequence.

- 21. (Currently Amended) A pumping system according to claim 17, wherein the actuating fluid is water.
- 22. (Currently Amended) A pumping system according to claim 21, wherein the supply means device comprise includes a water reservoir at an elevated location in order to supply the water at the appropriate pressure head.
- 23. (Currently Amended) A pumping system according to claim 15, wherein the delivery of the actuating fluid to the actuating region is at an opposed end to the port through which pumped fluid enters into and discharges from the pumping chamber.
- 24. (Currently Amended) A pumping system according to claim 15, wherein the outlet of the actuating fluid from the actuating region is also at an opposed end to the port through which pumped fluid enters into and discharges from the pumping chamber.

## 25. (Currently Amended) A pumping system comprising:

two pumps, each pump being in accordance with claim 1;

a delivery apparatus for delivering pumped fluid to the pumping chambers in timed sequence for causing the pumping chambers to undergo an intake stroke; and

an apparatus for supplying actuating fluid to the actuating regions in timed sequence to cause the tube structures to laterally collapse whereby the pumping chambers undergo a discharge stroke,

wherein the A pumping system according to claim 15 comprising two pumps operating are operated sequentially such that the pumping chamber of one pump performs an intake stroke while the pumping chamber of the other pump performs a discharge stroke, and vice versa.

- 26. (Currently Amended) A pumping system according to claim 25, wherein the sequential operation of the two pumps is such that a generally uninterrupted supply of pumped fluid is expelled from the pumping system.
- 27. (Currently Amended) A pumping system according to claim 25, wherein the duration of the discharge stroke is longer than the duration of the intake stroke.
- 28. (Currently Amended) A pumping system according to claim 25, wherein one pump completes its intake stroke and commences its discharge stroke while the other pump is completing its discharge stroke.
- 29. (Currently Amended) A pumping system according to claim 25, wherein the discharge intake stroke of one pump is completed by the time the discharge stroke from the other pump is completed and a flow from the discharge stroke is equal in flow to the desired flow of pump fluid from the pumping system.
- 30. (Currently Amended) A pumping system according to claim 25, wherein the two pumps have a common delivery means—device and a common supply means device, with appropriate valve systems controlling the sequence of operation.

- 31. (Currently Amended) A pumping system according to claim 25, wherein the or-each pump is oriented so that the closed end of the tube structure is elevated in relation to the other end thereof.
- 32. (Currently Amended) A pumping system according to claim 25, wherein the delivery and exit of the actuating fluid to the actuating region is adjacent the closed end.
- 33. (Currently Amended) A pump for conveying a pumped fluid using an actuating fluid, the pump comprising:
  - a rigid outer casing defining an interior space; and-
- a flexible tube structure accommodated in the interior space, the an interior of the tube structure defining a pumping chamber for receiving pumped fluid, the tube structure being movable between laterally expanded and collapsed conditions for varying the volume of the pumping chamber thereby to provide discharge and intake strokes, one end of the tube structure being closed and the other end communicating with a port through which pumped fluid ean—enters into and discharges from the pumping chamber as the pumping chamber performs the intake and discharge strokes, the a region of the interior space surrounding the tube structure defining an actuating region for receiving actuating fluid, the tube structure being moveably supported and maintained in a taut condition, the pumping chamber being adapted configured to receive pumped fluid to cause the tube structure to move towards the expanded condition and the pumping chamber thereby undergoing an intake stroke, the pumping chamber undergoing a discharge stroke upon collapsing of the tube structure in response to the an action of

actuating fluid in the actuating region.

34. (Currently Amended) A pump according to claim 33, wherein the tube

structure is substantially inelastic.

35. (Currently Amended) A pump according to claim 35-33, wherein the port

through which fluid enters the pumping chamber is at an opposed end to where the

actuating fluid enters the pump.

36. (Currently Amended) A pumping system comprising:

at least two pumps, each pump being in accordance with claim 1; having a

pumping chamber accommodated in an actuating region,

a delivery means device for delivering pumped fluid to each pumping

chamber in timed sequence, causing each pumping chamber to undergo an intake

stroke-; and

a means device for supplying actuating fluid to each actuating region in

timed sequence to cause a respective tube structure of the pumping chamber to

laterally collapse and the pumping chamber undergoing a discharge stroke,

whereby the sequential operation of the at least two pumps expels a generally

uninterrupted supply of pump fluid from the pumping system.

37. (Canceled)

38. (Canceled)

- 39. (Currently Amended) A pumping system according to claim 38–36, wherein the closed end of the pumping chamber is elevated in relation to the other end thereof.
- 40. (Currently Amended) A method of operating a pumping system in accordance with claim 36, wherein the a duration of the discharge stroke of one pump is longer than the a duration of the intake stroke of the other pump, and vice versa, whereby, when operated sequentially, the pumping system delivers a generally uninterrupted supply of fluid.
- 41. (Currently Amended) A pump for conveying a pumped fluid using an actuating fluid, the pump comprising:
  - a rigid outer casing defining an interior space, and
- a tube structure accommodated in the interior space, the tube structure having one end closed and in an elevated position in to-relation to the other end, which communicates with a port through which pumped fluid ean-enters into and discharges from the pumping chamber, the tube structure being moveably supported and maintained in a taut condition, the interior of the tube structure defining a pumping chamber for receiving pumped fluid, the tube structure being movable between laterally expanded and collapsed conditions for varying the volume of the pumping chamber thereby to provide discharge and intake strokes, the—a\_region of the interior space surrounding the tube structure defining an actuating region for receiving actuating fluid, the pumping chamber being adapted configured to receive pumped fluid to cause the tube structure to move towards the expanded condition and the pumping chamber thereby undergoes an intake stroke,

Application No. 10/522,732 Attorney Docket No. 15359-00001/US

the pumping chamber undergoing a discharge stroke upon collapsing of the tube

structure in response to the action of actuating fluid in the actuating region.

42. (Currently Amended) A pump according to claim 41, wherein the

actuating fluid enters the actuating region adjacent the closed end of the pumping

chamber.

43. (Currently Amended) A pump according to claim 41, wherein the tube

structure is flexible and substantially inelastic.

44. (Cancelled).

45. (Cancelled).

46. (Cancelled).